



Ceiling luminaires · Downlights

Family of LED downlights, available in two sizes and two exterior finishes. The thick-walled, crystal glass brings sparkle and added interest to any ceiling surface while the inner frosted section provides glare control and minimizes the direct view of the LED source. The compact, shallow housing is ideal for areas with low ceiling heights such as lobbies and corridors. Provided with electronic driver.

Crystal glass diffuser, partially frosted with screw neck
Reflector made of pure anodized aluminum · Die-cast aluminum housing

Select the desired exterior finish by using appropriate code number as suffix

- White Code number **.1**
- Stainless steel Code number **.2**

LED color temperatures: 2700K, 3000K, 3500K, 4000K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only
Refer to page 185 for more information



Select the desired exterior finish by using appropriate code number as suffix.



White
Code number **.1**



Stainless steel
Code number **.2**



· A ·

Downlight			
	LED	A	B
50 568	11.5W	5 5/8	3 1/4
50 570	17.0W	7	3 3/4