



## Pendant luminaires

Unshielded LED pendant luminaires in a classic cylinder shape, available in various sizes and light outputs. These timeless pendants are made of hand-blow, three-ply opal glass combined with state-of-the-art lighting technology for a luminaire well suited for any interior space.

Canopy mounted electronic driver.

Hand-blown, three-ply opal glass, satin matte finish  $\cdot$  Internal acrylic diffuser Metal housing and canopy  $\cdot$  White or black connecting cable

Select the desired trim finish by using appropriate code number as suffix

- White Code number .1
- Chrome Code number .3

LED color temperatures: 2700 K, 3000 K, 3500 K, 4000 K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires – see page 186. Further LED technical data including luminous flux, CRI, service life, and dimming and electrical characteristics are provided on the individual luminaire specification sheets, available at www.bega-us.com.

NRTL listed to North American Standards, interior use only Refer to page 185 for more information



Canopy


Select the desired trim finish by using appropriate code



White, white cable Code number .1



Chrome, black cable Code number .3



Pendant · Unshielded				
	LED	Α	В	L
6 606	11.6W	4 3/4	11	73
6 607	22.8W	5 7/8	13¾	75
6 608	28.2 W	7 1/8	16 1/2	77
6 609	52.8 W	8 5/8	21 1/8	81

166